

BUTYL RUBBER SEALING TAPE

PRODUCT DESCRIPTION

JDHT BG-B butyl sealing tape is a self-adhesive tape, with PVDF, aluminum foil film or stich bonded fabric as cover, consists butyl rubber as adhesive layer, release liner on underside, which is applicable for various substrates.

CHARACTERISTICS / ADVANTAGES

- 1 Practical, various types available for different projects;
- 2 Easy to use, portable, cost saving, good pertinence;
- 3 Wide range of applications, such as home decorations, waterproofing maintenance, large scale waterproofing joints etc.

USES

- Detailing sealing
- Roofs
- Exterior walls
- Window frames
- Low pressure pipes maintenance

PRODUCT INFORMATION

Appearance / Color black ■

Shelf life 1 year

Thickness 1.0mm

Width 50mm,100mm,200m

Persistence,min ≥ 20

Thermostability, 80°C, 2h No flowing, cracks nor deformation

Flexibility at low temperature,-40°C no cracks

Bonding strength under shear N/mm

Membrane ≥ 2.0

Peel strength N/mm

Membrane ≥ 0.4

Cement mortar board ≥ 0.6

Colored steel ≥ 0.6

Peel strength retention rate %

Thermostability, 80°C, 168h

Membrane,Cement mortar,Colored steel ≥ 80

Alkali treatment, Saturated calcium hydroxide, 168h

Membrane,Cement mortar,Colored steel ≥ 80

Soaking, 168h

Membrane,Cement mortar,Colored steel ≥ 80