
BUTYL RUBBER SEALANT

PRODUCT DESCRIPTION

JDHT BG-J butyl rubber sealant consists of asphalt and various additives together with butyl modifier and solvents. Mainly used for strengthening adhesion between substrates and membranes, features enclosure of mortar base capillary and vapor barrier.

CHARACTERISTICS / ADVANTAGES

- 1 Easy to apply, ready to use;
- 2 Excellent adhesion, applicable for various substrates, such as concrete, metal, plastic, etc. both on wet and dry surfaces;
- 3 Great penetration property, achieve surface sealing effect by penetrate and healing surface defect;
- 4 Good compatibility property, can be combined with various membranes or coatings to increase adhesion performance with surfaces;
- 5 Eco-friendly, contains no volatile organic solvents, harmless, non-pollution.

USES

- Sealant
- prior butyl rubber membrane paving

PRODUCT INFORMATION

Appearance / Color	black ■
Shelf life	6 months from date of manufacture
Packaging Dimension	20kg, drum
Standard	Q/LJH 0023-2019
Viscosity mPa.s	Specified value $\pm 30\%$
Surface drying time, h \leq	4
Solid contents, % \geq	40
Peeling force between membranes N/mm \geq	0.8
Peeling strength after soaking N/mm \geq	0.8
Thermostability	80°C no flowing
Flexibility at low temperature	-5°C no cracks
